

FLUORESCENT STARTERS Starters for Single and Series Circuits

| | | eral Data: | | |
|-----------------------|---------------------------------|---------------------------|---------------------------|--|
| | | Product Benefits: | | |
| | | Faulty Lamps | They reliably disconnect | |
| | | | burnt-out or faulty lamps | |
| | | Instantly Ready | For operation when red | |
| | | | button is pressed | |
| | | Automatic Cutout | Protects the choke and | |
| | | Circuit | starter itself | |
| | | Ensure Reliable | The starter should be | |
| | | Ignition and | replaced after every four | |
| | Product | Operation | lamp replacements | |
| | Features: | | | |
| Available in: | Single Operation (4-80 W) | Typical | | |
| | Series Operation (4-22 W) | Applications: Lighting | *Line with fluerenent | |
| | 4 X the Amout of a Conventional | | *Use with fluorescent | |
| | Stater | | lamps | |
| Temperature Range for | | | | |
| Relaible Cut-Out: | -20 °C to +80 °C | | | |

Colour Type:

| | Sky White | Cool D | aylight | Daylight | Cool | White | White | Warm | White | INTERNA | Special Light Colours |
|-------|--------------|----------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|-----------------------------|
| Code: | | 865 6 500 K | 965 5 400K | 954 5 400K | 840 4 000K | 940 4 000K | 835 3 500K | 830 3 000K | 830 3 000K | 827 2 700K | |
| | | | | | | | | | | | |



Technical Information and Photographs from OSRAM Selected Information has been Edited by ACTOM Electrical Products


Address: 4 Branch Road, Germiston 1401, P.O. Box 678, Germiston 1400

Tel: +27 11 878 3050



FLUORESCENT STARTERS Starters for Single and Series Circuits





ST 111 LONGLIFE 2-80 W

5 **25 25**

ST 111 LONGLIFE 2-80 W

Product Information:

| Product Description | W | V | Length | Diameter | Rated Ave Life |
|--------------------------------------------------------------|--------|-----|--------|----------|------------------------------|
| | | | (mm) | (mm) | (h) |
| ST 111 LONGLIFE 4-80 W, Single Operation (code:58128) | 4-80 W | 230 | 40.3 | - | 4 x a Conventional Stater |
| ST 151 LONGLIFE 4-22 W, Series Operation (code:58134G) | 4-22 W | 230 | 40.3 | - | 4 x a Conventional Stater |



Technical Information and Photographs from OSRAM Selected Information has been Edited by ACTOM Electrical Products

Address: 4 Branch Road, Germiston 1401, P.O. Box 678, Germiston 1400

Tel: +27 11 878 3050



Complete your Project:

Please select the items you require and we will be in touch

Cables and Wires:

Indoor Outdoor General Other Let an ACTOM Specialist Contact you

Lighting:

Indoor Outdoor General Other Let an ACTOM Specialist Contact you

Transformers (Distribution):

Indoor Outdoor General Other Let an ACTOM Specialist Contact you

Accessories:

Indoor Outdoor General Other Let an ACTOM Specialist Contact you

Specific Information:

Address: 4 Branch Road, Germiston 1401, P.O. Box 678, Germiston 1400



For more Information on this Product Please Send us the Folowing

Product Information:

Product Name:

Quantity:

Project Name:

Date the Product is required:

Your Contact Information:

Name and Surname:

Company:

Email:

Phone Number:

Province:

Thank You

For having a Look at this Product

Please send this PDF back to us with all your Information



Scan the QR Code to visit our Website:

Address: 4 Branch Road, Germiston 1401, P.O. Box 678, Germiston 1400

Tel: +27 11 878 3050